Applicant: Gerhard Fritz, et al. Attorney's Docket No.: 14603-025US1 / P2003, 0926

US N

Serial No. : 10/584,668

Filed : June 27, 2006

Page : 2 of 5

## AMENDMENTS TO THE CLAIMS:

This listing of claims replaces all prior versions and listings of claims in the application:

## LISTING OF CLAIMS:

1. (Currently Amended) An energy consumption meter arrangement, having

a first input (4) for feeding a signal derived from a voltage (44), to which first input (4) a first analog- to-digital converter (3) is connected,

a second input (2) for feeding a signal derived from a current (4), to which second input (2) a second analog-to-digital converter (4) is connected,

a multiplier (7), which combines the outputs of the two analog-to-digital converters (3, 4) with one another,

a phase evaluation block (9) having two inputs, which are coupled to the first and the second input (4,2) of the energy consumption meter arrangement for the purpose of measuring a phase difference  $(\Delta \phi)$ , and having an output, which is coupled to a phase correction block (6), and

the phase correction block (θ), which is coupled to an output of one of the two analog-to digital converters (4), designed for correcting the phase difference (Δφ) of the digitized signal derived from a current (I) or a voltage (Ψ).

- 2. (Currently Amended) The energy consumption meter arrangement as claimed in claim 1, characterized in that the phase evaluation block (9) comprises means for permanently storing a phase correction value (17).
- 3. (Currently Amended) The energy consumption meter arrangement as claimed in claim 1 or 2, characterized in that in each case one limiting amplifier (10, 11) is provided which

Applicant : Gerhard Fritz, et al. Attorney's Docket No.: 14603-025US1 / P2003, 0926

Scrial No.: 10/584,668

Filed : June 27, 2006

Page : 3 of 5

couples in each case one input of the energy consumption meter arrangement (1, 2) to in each case one input of the phase evaluation block (9).

4. (Currently Amended) The energy consumption meter arrangement as claimed in one of elaims 1-to 3 claim 1, characterized in that the first and the second analog-to-digital converters (3, 4) are each in the form of sigma-delta converters.

- 5. (Currently Amended) The energy consumption meter arrangement as claimed in one of-elaims-1-to-4 claim 1, characterized in that an integrator (8) is provided which is connected downstream of the multiplier (7).
- 6. (Currently Amended) The energy consumption meter arrangement as claimed in one of elaims 1-to-5 claim 1, characterized in that the first and the second analog-to-digital converters (3, 4), the phase correction block (6) and the phase evaluation block (9) are designed using integrated circuit technology.
- 7. (Currently Amended) The energy consumption meter arrangement as claimed in ene of elaims 1 to 6 claim 1, characterized in that a nonconductively coupling transfer arrangement (14) is connected to the first input (1) and/or to the second input (2) for the purpose of coupling-in the signal derived from a voltage (14) and/or from a current (17).
- 8. (Currently Amended) The energy consumption meter arrangement as claimed in claim 7, characterized in that the nonconductively coupling transfer arrangement (14) is in the form of a transformer.
- (Currently Amended), The energy consumption meter arrangement as claimed in one of claims 1 to 8 claim 1, characterized in that a means for generating a test signal (46) is

Applicant: Gerhard Fritz, et al. Attorney's Docket No.: 14603-025US1 / P2003, 0926

US N

Serial No.: 10/584,668 Filed : June 27, 2006

Page : 4 of 5

provided which is coupled to the first and the second input (1, 2) of the energy consumption meter arrangement.